

# Kitemark™ Certificate

This is to certify that:

Olympia Electronics  
N. Lakasas - P. Arvanitidis S.A.  
72nd klm Old Highway  
Thessaloniki Katerini  
Eginio, Pieria  
P.C 60300  
Greece

Holds Certificate Number:

KM 640081

In respect of:

**BS EN 60598-2-22**  
**Emergency luminaires**

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions governing the use of the Kitemark, as may be updated from time to time by BSI Assurance UK Ltd (the "Conditions"). All defined terms in this Certificate shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Certificate provided at or from the above address.

For and on behalf of BSI:

Shahm Barhom, Group Product Certification Director

First Issued: 2016-01-14

Latest Issue: 2023-06-21

Effective Date: 2023-06-21

Expiry Date: 2025-01-18



Page: 1 of 41

# Kitemark™ Certificate

No. KM 640081

## Emergency Luminaires to BS EN IEC 60598-2-22:2022 in conjunction with BS EN IEC 60598-1:2021

KLD and KLIN range of Emergency/Exit Luminaires

Rated: 220-240 V, 50/60 Hz, Class II

BSI Test Report Number 3118648 and 3873722 Rev 2

Model	Rating	Duration	IP	Assembly type
KLD-30/ST	220-240 V AC/50-60 Hz	3 hours	IP54	Self-contained, recessed or surface ceiling/wall mounted emergency exit sign
KLD-30/ST/ADR	220-240 V AC/50-60 Hz	3 hours	IP54	Self-contained, recessed or surface ceiling/wall mounted emergency exit sign
KLD-22/ST	220-240 V AC/50-60 Hz	3 hours	IP54	Self-contained, recessed or surface ceiling/wall mounted emergency exit sign
KLD-22/ST/ADR	220-240 V AC/50-60 Hz	3 hours	IP54	Self-contained, recessed or surface ceiling/wall mounted emergency exit sign
KLR-20/ST	220-240 V AC/50-60 Hz	3 hours	IP54	Self-contained, recessed or surface ceiling/wall mounted emergency exit sign
KLR-20/ST/ADR	220-240 V AC/50-60 Hz	3 hours	IP54	Self-contained, recessed or surface ceiling/wall mounted emergency exit sign
KLIN-20/ST/ADR	220-240 V AC/50-60 Hz	3 hours	IP54	Self-contained, recessed or surface ceiling/wall mounted emergency luminaire
KLIN-20/ST	220-240 V AC/50-60 Hz	3 hours	IP54	Self-contained, recessed or surface ceiling/wall mounted emergency luminaire

Accessories for installation tested in this report:

Bracket code	Description	Supplied with luminaire?
N/A	Wall mounting	Yes
N/A	Ceiling mounting	Yes
A-2133	Wall mounting	No
A-2520/PL/ST	Recess mounting	No
A-2132	Ceiling mounting	No
A-2136	Hanging installation	No

First Issued: 2016-01-14

Latest Issue: 2023-06-21

Effective Date: 2023-06-21

Expiry Date: 2025-01-18

Page: 5 of 41

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

# Kitemark™ Certificate

No. KM 640081

## Emergency Luminaires to BS EN IEC 60598-2-22:2022 in conjunction with BS EN IEC 60598-1:2021

KLD and KLIN range of Emergency/Exit Luminaires

Rated: 220-240 V, 50/60 Hz, Class II

BSI Test Report Number 3118648 and 3873722 Rev 2

Model	Rating	Duration	IP	Assembly type
FRN KLD-30/ST	220-240 V AC/50-60 Hz	3 hours	IP54	Self-contained, recessed or surface ceiling/wall mounted emergency exit sign
FRN KLD-30/ST/ADR	220-240 V AC/50-60 Hz	3 hours	IP54	Self-contained, recessed or surface ceiling/wall mounted emergency exit sign
FRN KLD-22/ST	220-240 V AC/50-60 Hz	3 hours	IP54	Self-contained, recessed or surface ceiling/wall mounted emergency exit sign
FRN B2308U = KLD-22/ST/ADR	220-240 V AC/50-60 Hz	3 hours	IP54	Self-contained, recessed or surface ceiling/wall mounted emergency exit sign
FRN KLR-20/ST	220-240 V AC/50-60 Hz	3 hours	IP54	Self-contained, recessed or surface ceiling/wall mounted emergency exit sign
FRN KLR-20/ST/ADR	220-240 V AC/50-60 Hz	3 hours	IP54	Self-contained, recessed or surface ceiling/wall mounted emergency exit sign
FRN KLIN-20/ST/ADR	220-240 V AC/50-60 Hz	3 hours	IP54	Self-contained, recessed or surface ceiling/wall mounted emergency luminaire
FRN KLIN-20/ST	220-240 V AC/50-60 Hz	3 hours	IP54	Self-contained, recessed or surface ceiling/wall mounted emergency luminaire

Accessories for installation tested in this report:

Bracket code	Description	Supplied with luminaire?
N/A	Wall mounting	Yes
N/A	Ceiling mounting	Yes
A-2133	Wall mounting	No
A-2520/PL/ST	Recess mounting	No
A-2132	Ceiling mounting	No
A-2136	Hanging installation	No

First Issued: 2016-01-14

Latest Issue: 2023-06-21

Effective Date: 2023-06-21

Expiry Date: 2025-01-18

Page: 25 of 41

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).